



ONLINE /OFFLINE Ups Technical Specification

CAPACITY	1000VA,1500VA,2000VA, 2500VA	2500VA,3000VA,3500VA4000VA 4500VA,5000VA
DC Voltage	12/24V/36/48V	24V/48V/60V/72V
INPUT		
Voltage Range	180V - 270V ±5%	
Frequency	50 ± 1% Hz	
Charging Ampere	10A	
Mains to inverter Shift	Automatic	
OUTPUT		
Voltage In Battery Mode	230V	
Frequency	50 ± 1% Hz	
Wave foam	Sinewave	
Duty	Continuous	
Battery Type	Lead acid,Gel,Smf	
Load	0.8 PF	
Display Indications	Input voltage, Output voltage, Battery voltage Load in watts,Trip, Battery charging Ampere Battery low , Over Load In Watts	
Specical Features	SINE WAVE OUTPUT,LCD DISPLAY,SOLAR OPTION	
Solid State Protections	Fault Trip Alarm for Battery Low, Output Overload Short Circuit, Over temperature	
Environment		
Storage Temperature	5 °C - 55 °C	
Humidity	Up to 85% RH (Non Condensing)	
Noise Level	<60db AT 1 meter	
By – Pass Automatic	Provided	
Fixing	BUSH/WHEEL	